FLOODED DEEP CYCLE BATTERY

6 FS 305-HC-N





Series	FLA FS SERIES	Warranty	1 Year
Volts	6	Design	902
Cells	3	Plates/Cell	17
Terminal Type		DT	
Included Hardware		Stainless Steel K-Lock Nut	
Size & Threads		5/16"-18	

Charge | Discharge

Charge Voltage Range	2.45-2.5 V/cell @ 25°C (77°F)
Float Voltage Range	2.25 V/cell @ 25°C (77°F)
Recommended Charge Current	40 A
Maximum Charge Current	65 A
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

Capacity

Cold Crank Amps (CCA) 0°F / -18°C	878
Marine Crank Amps (MCA) 32°F / 0°C	1097
Reserve Capacity (RC @ 25A)	619 Minutes
Reserve Capacity (RC @ 75A)	163 Minutes

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	75%	50%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	**410 AH**	**4.10 A**
@ 72 Hour Rate	**403 AH**	**5.60 A**
@ 50 Hour Rate	**381 AH**	**7.62 A**
@ 20 Hour Rate	**320 AH**	**16.00 A**
@ 15 Hour Rate	**304 AH**	**20.27 A**
@ 10 Hour Rate	**282 AH**	**28.16 A**
@ 8 Hour Rate	**275 AH**	**34.4 A**
@ 5 Hour Rate	**253 AH**	**50.56 A**
@ 1 Hour Rate	**128 AH**	**128.00 A**


Specifications

Weight	44 kg	97 lbs
Length	300 mm	11.85"
Width	181 mm	7.13"
Height Incl. Term.	362 mm	14.25"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Electrolyte Reserve	44 mm	1.75"
Container	Polypropylene	
Cover	Polypropylene	
Handles	None. Optional 305 Battery Sling	


Cycle Life vs. Depth of Discharge




Voltage vs. Depth of Discharge

DISCHARGE	0%	25%	50%	75%	100%
20 HR AH RATE	2.10 V	2.07 V	2.00 V	1.92 V	1.75 V
10 HR AH RATE	2.10 V	2.06 V	1.98 V	1.89 V	1.75 V
3 HR AH RATE	2.10 V	2.03 V	1.95 V	1.86 V	1.75 V
1 HR AH RATE	2.10 V	2.01 V	1.93 V	1.84 V	1.75 V

Detailed Illustration





OPTIONAL: 305 BATTERY SLING

BATTERY COUNCIL INTERNATIONAL

Designed in compliance with applicable BCI, DIN, BS & IEC standards.
Tested in compliance to BCI & IEC standards.

intertek 0122624

Rev.#3 | June 2026