

LIFEPO4 LITHIUM BATTERY

G24-130LFP









Series	G-SERIES LFP	Warranty	See Warranty Terms
Volts	24	Design	8D
Terminal Type		M8	
Included Hardware		M8 stainless bolts & washers	

Charge | Discharge

Charge Voltage Range	28.0 - 29.2V
Recommended End of Discharge Voltage	24.0 V
End of Discharge Protection Voltage	20.0 V
Recommended Charge Voltage	28.8 V
Recommended Charge Current	

0~10°C (32-50°F)	0.2C	26A
10~35°C (50-95°F)	0.5C	65A
35~50°C (95-122°F)	0.2C	26A

Charge Mode:
• Charge at recommend voltage & current by temperature until charge current drops to ≤ 0.05C (CC,CV)
• DO NOT USE TEMPERATURE COMPENSATION
• No BTS (Battery Temperature Sensor)

Max Continuous Charge Current	130 A
Max Continuous Discharge Current	130 A
Peak Discharge Current (10 min)	200 A
Charge Temperature Range	0°C~55°C (32~131°F)
Discharge Temperature Range	-20°~60°C (-4~140°F)
Storage Temperature Range	-5°~45°C (23~113°F)

Capacity

Nominal Capacity	130 AH
Total Energy	3.33 kWh
Nominal Voltage	25.6 V

Designed for Golf, Light EV & Motive Power Applications

Safety

- Cylindrical LiFePO4 cells [ITR26-70/40E 4.0Ah, 26700] (UL1642)
- IEC62133 (cell), IEC62619(cell), UN38.3 (cell/pack)
- ROHS (cell), CE system certification, IP65 Rating

Design

- Standard-size (BCI) ABS container for easy VRLA replacement
- Fast charge/discharge performance
- 200A / 10 minute peak discharge
- Display & integrated controls
- Visual state-of-charge (SOC)
- External fuse access
- Bluetooth Connectivity & dedicated IOS & Android App
- Maintenance-free operation

Battery Management System (BMS)

- Integrated hardware BMS inside
- Independent charge & discharge protection
- Balance Protection
- Short-Circuit Protection, Over-Voltage Protection, Low-Voltage Protection, Over-Current Protection, Low-Temperature Protection, Over-Temperature Protection

➦ **24V LFP Profile**


Specifications

Weight	30.0 kg	66.1 lbs
Length	522 mm	20.55"
Width	268 mm	10.55"
Height	219 mm	8.62"
Height Incl. Term.	232 mm	9.13"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Rope / Plastic Handle
Internal BMS Model	8S200ATX-V2
Expected Cycle Life	>6000 @ 80% DOD, >3000 @ 100% DOD
Series Connection	2 UNITS MAX (48V)
Parallel Connection	4 UNITS MAX (48V) or 6 UNITS MAX (24V)
Connectivity	Up to 2S4P (in 48V configuration) or 1S6P (in 24V configuration)

Detailed Illustration



ISO9001 ISO14001 OHSAS18001

Rev.#1 | June 2025