AGM VRLA DEEP CYCLE BATTERY

S12-170AGM-RE





Series	VRLA AGM-S	Warranty	See Warranty Terms
Volts	12	Design	SPEC
Cells	6		
Terminal Type	F10(M8)		
Included Hardware	M8 stainless bolts & washers & TP08 adapter		
Size & Thread	M8		

Charge | Discharge

Charge Voltage Range	14.7V @ 25°C (77°F)
Float Voltage Range	13.8V @ 25°C (77°F)
Recommended Charge Current	30 A
Maximum Charge Current	45 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)
Internal Resistance	4 mΩ

Capacity

Cold Crank Amps (CCA) 0°F / -18°C	715

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	102%	100%	85%	65%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	**170 AH**	**1.7 A**
@ 20 Hour Rate	**159 AH**	**7.95 A**
@ 10 Hour Rate	**150 AH**	**15.0 A**
@ 5 Hour Rate	**131 AH**	**26.2 A**

Cut Off Voltage	Constant Current Discharge					
	1 hr	2 hr	3 hr	5 hr	8 hr	10 hr
VPC	80.1	47.6	37.5	25.5	18.0	15.0

Specifications


Weight	43 kg	95 lbs
Length	327 mm	12.9"
Width	180 mm	7.09"
Height Incl. Term.	276 mm	10.9"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.


Container	ABS
Cover	ABS
Handles	Nylon Strap

- Plastics are UL94 HB (UL94 V0 available)
- Valve regulated design with integral flame arrestor
- Non-hazardous, Non-spillable


Cycle Life vs. Depth of Discharge



Capacity vs. Temperature



Detailed Illustration



Designed in compliance with applicable BCI, DIN, BS & IEC standards.
Tested in compliance to BCI & IEC standards.

Rev.#2 | August 2024