
FLOODED DEEP CYCLE BATTERY

S6 L16-EX





Series	FLA SERIES 4500	Warranty	4 Years
Volts	6	Design	L16
Cells	3	Plates/Cell	11
Terminal Type	LT		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18		
Cables	Optional: 19" 4/0 interconnect cable		

Charge | Discharge

Charge Voltage Range	2.45-2.5 V/cell @ 25°C (77°F)
Float Voltage Range	2.25 V/cell @ 25°C (77°F)
Recommended Charge Current	45 A
Maximum Charge Current	70 A
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

Capacity

Cold Crank Amps (CCA) 0°F / -18°C	871
Marine Crank Amps (MCA) 32°F / 0°C	1088
Reserve Capacity (RC @ 25A)	890 Minutes
Reserve Capacity (RC @ 75A)	297 Minutes

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	75%	50%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	**479 AH**	**4.79 A**
@ 72 Hour Rate	**453 AH**	**6.29 A**
@ 50 Hour Rate	**429 AH**	**8.57 A**
@ 20 Hour Rate	**371 AH**	**18.55 A**
@ 15 Hour Rate	**345 AH**	**23.00 A**
@ 10 Hour Rate	**330 AH**	**33.02 A**
@ 8 Hour Rate	**319 AH**	**39.88 A**
@ 5 Hour Rate	**297 AH**	**59.36 A**
@ 1 Hour Rate	**167 AH**	**166.95 A**

Specifications


Weight	59 kg	130 lbs
Length	318 mm	12.5"
Width	181 mm	7.13"
Height Incl. Term.	425.5 mm	16.75"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Electrolyte Reserve	57 mm	2.25"
Container	High Density Polypropylene	
Cover	High Density Polypropylene	
Handles	Rope / Plastic Handle	

- Plastics are UL94 HB (UL94-V2 available)
- Plastics are impact copolymer rated to ASTM D256, D5420
- Vented design with integral flame arrestor vent caps


Cycle Life vs. Depth of Discharge



Voltage vs. Depth of Discharge

DISCHARGE	0%	25%	50%	75%	100%
20 HR AH RATE	2.10 V	2.05 V	2.02 V	1.96 V	1.75 V
6 HR AH RATE	2.10 V	2.04 V	2.00 V	1.95 V	1.75 V
1 HR AH RATE	2.10 V	2.03 V	1.99 V	1.94 V	1.75 V

Detailed Illustration



Designed in compliance with applicable BCI, DIN, BS & IEC standards.
Tested in compliance to BCI & IEC standards.

intertek 0122624

Rev.#3 | August 2024